Game Semantics for Paraconsistent Logics

Can BAŞKENT

Department of Computer Science, University of Bath

can@canbaskent.net canbaskent.net/logic

November 19th, 2015

Midlands Logic Seminar, Birmingham.



◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 …



Outlook of the Talk

- Logic of Paradox
- First-Degree Entailment
- Relevant Logic
- Connexive Logic
- Belnap's 4-valued Logic
- Translation to S5 Modal Logic

< 行 →

-

A logic is **paraconsistent** if contradictions do not entail everything.

In a paraconsistent logic, it is possible to have true contradictions.

How to understand paraconsistency from a game semantical point of view?



< 17 ▶

Why Paraconsitency?

- A logic is **paraconsistent** if contradictions do not entail everything.
- In a paraconsistent logic, it is possible to have true contradictions.
- How to understand paraconsistency from a game semantical point of view?



Classical Game Semantics

During the semantic verification game, the given formula is broken into subformulas by **two** players (Abelard and Heloise) **step by step**, and the game **terminates** when it reaches the propositional atoms.

If we end up with a propositional atom which is true, then Eloise the verifier wins the game. **Otherwise**, Abelard the falsifier wins. We associate **conjunction with Abelard**, **disjunction with Heloise**.

A win for the verifier is when the game terminates with a true statement. The verifier is said to have a winning strategy if she can force the game to her win, regardless of how her opponent plays.



< 17 ▶

< ∃ >

Classical Game Semantics

Just because the game may end with a true/false atom does not necessarily suggest the truth/falsity of the given formula in general.

In classical logic, however, the major result of game theoretical semantics states that the verifier has a winning strategy **if and only if** the given formula is true in the model.



Classical LP FDE RR Connexive B4 LP vs S5 Conclusion References

Classical Games

Classical semantic games are

- Two-player,
- Determined,
- Sequential,
- Zero-sum,
- Complete: winning strategies necessarily and sufficiently guarantee the truth value.

Question How do these attributes of semantical games depend on the underlying logical structure? How can we give game semantics for *deviant* logics?

< □ > < A > >

Classical	LP	FDE	Connexive	B4	LP vs S5	Conclusion	References

Logic of Paradox



Game Semantics for Paraconsistent Logics

Can Başkent

Consider Priest's Logic of Paradox (LP) (Priest, 1979).

LP introduces an additional truth value *P*, called *paradoxical*, that stands for both true and false.





We define the verification game as a tuple $\Gamma = (\pi, \rho, \delta, \sigma)$ where

- π is the set of players,
- ρ is the set of well-defined game rules,

- δ is the set of designated truth values: the truth values preserved under validities: they determine the theorems of the logic.

- σ is the set of positions: subformula and player pairs.

It is possible to extend it to concurrent games as well.



< 17 ▶

The introduction of the additional truth value *P* requires

an additional player in the game, let us call him *Astrolabe* (after Abelard and Heloise's son).

Since we have three truth values in LP, we need three players forcing the game to their win. If the game ends up in their truth set, then that player wins.

Then, how to associate moves with the connectives?



Game Rules for LP

Denote this system with *GTS*^{LP}.

р	whoever has p in their extension, wins
$\neg F$	Abelard and Heloise switch roles
$F \wedge G$	Abelard and Astrolabe choose between
	F and G simultaneously
$F \lor G$	Eloise and Astrolabe choose between
	F and G simultaneously



< ロ > < 部 > < 目 > <</p>

Classical LP FDE RR Connexive B4 LP vs S5 Conclusion References An Example

Consider the conjunction. Take the formula $p \land q$ where p, q are P, F respectively. Then, $p \land q$ is F.



Abelard makes a move and chooses q which is false. This gives him a win. Interesting enough, Astrolabe chooses p giving him a win.

In this case both seem to have a winning strategy. Moreover, the win for Abelard does not entail a loss of BATT Astrolabe.

Correctness

Theorem

In GTS^{LP} verification game for φ ,

- Eloise has a winning strategy if φ is true,
- Abelard has a winning strategy if φ is false,
- Astrolabe has a winning strategy if φ is paradoxical.



- E - >

Theorem

In a GTS^{LP} game for a formula φ in a LP model *M*,

- If Eloise has a winning strategy, but Astrolabe does not, then φ is true (and only true) in M,
- If Abelard has a winning strategy, but Astrolabe does not, then φ is false (and only false) in M,
- If Astrolabe has a winning strategy, then φ is paradoxical in in *M*.



∃ >

Classical	LP	FDE	Connexive	B4	LP vs S5	Conclusion	References

First-Degree Entailment



Game Semantics for Paraconsistent Logics

Can Başkent

-

First-Degree Entailment

Semantic valuations are *functions* from formulas to truth values.

If we replace the valuation function with a valuation *relation*, we obtain *First-degree entailment* (FDE) which is due to Dunn (Dunn, 1976).

We use $\varphi \mathbf{r} \mathbf{1}$ to denote the truth value of φ (which is 1 in this case).

Since, **r** is a relation, we allow $\varphi \mathbf{r} \emptyset$ or $\varphi \mathbf{r} \{0, 1\}$.

Thus, FDE is a paraconsistent (inconsistency-tolerant) and paracomplete (incompleteness-tolerant) logic.



< ∃ >

First-Degree Entailment

For formulas φ , ψ , we define **r** as follows.

$\neg \phi \mathbf{r}$ 1	iff	φ r 0
¬ φr 0	iff	φ rl
$(\varphi \land \psi)$ r 1	iff	φ r 1 and ψ r 1
$(\varphi \wedge \psi)\mathbf{r}0$	iff	φ r 0 or ψ r 0
$(\boldsymbol{\varphi} \lor \boldsymbol{\psi})\mathbf{r}1$	iff	φ r 1 or ψ r 1
$(\boldsymbol{\varphi} \lor \boldsymbol{\psi})\mathbf{r}0$	iff	φ r 0 and ψ r 0



Game Semantics for FDE

The truth values $\{0\}$, $\{1\}$ and $\{0, 1\}$ work exactly as the truth values *F*, *T*, *P* respectively in LP. In fact, LP can be obtained from FDE by introducing a restriction that no formula gets the truth value \emptyset .

Recall that for GTS^{LP}, we allowed parallel plays for selected players depending on the syntax of the formula: we associated conjunction with Abelard and Astrolabe, disjunction with Heloise and Astrolabe.



Game Semantics for FDE

For FDE, the idea is to allow each player play at each node.

Therefore, it is possible that both players (or none) may have a winning strategy.



< 177 ▶

< ∃ >

Consider two formulas with the following relational semantics: $\varphi \mathbf{r}0$, $\varphi \mathbf{r}1$ and $\psi \mathbf{r}1$. In this case, we have $(\varphi \land \psi)\mathbf{r}1$ and $(\varphi \land \psi)\mathbf{r}0$.

We expect both Abelard and Heloise have winning strategies, and allow each player make a move at each node.



Game Rules for FDE

р	whoever has p in their extension, wins
$\neg F$	players switch roles
$F \wedge G$	Abelard and Heloise choose between F and G
	simultaneously
$F \lor G$	Abelard and Heloise choose between F and G
	simultaneously



Theorem

In a GTS^{FDE} verification game for a formula φ , we have the following:

- Heloise has a winning strategy if φr1
- Abelard has a winning strategy if φr0
- No player has a winning strategy if φrØ



< 177 ▶

< ∃ >

Classical	LP	FDE	RR	Connexive	B4	LP vs S5	Conclusion	References

Relevant Logic



Game Semantics for Paraconsistent Logics

Can Başkent

• • • • • • • • • • • •

Routleys' Relevant Logic

An interesting way to extend the relational semantics is to add possible worlds to the model for negation. The idea is due to Routley and Routley (Routley & Routley, 1972). We call this system RR.

A *Routley model* is a structure (W, #, V) where W is a set of possible worlds, # is a map from W to itself, and V is a valuation defined in the standard way.

The semantics for RR is as follows.

$$\begin{array}{ll} V(w, \varphi \land \psi) = 1 & \text{iff} & V(w, \varphi) = 1 \text{ and } V(w, \psi) = 1 \\ V(w, \varphi \lor \psi) = 1 & \text{iff} & V(w, \varphi) = 1 \text{ or } V(w, \psi) = 1 \\ V(w, \neg \varphi) = 1 & \text{iff} & V(\#w, \varphi) = 1 \end{array}$$

Game Rules for RR

The game semantics for RR is given as follows.

(<i>w</i> , <i>p</i>)	whoever has p in their extension, wins
$(W, \neg F)$	switch roles, continue with $(\#w, F)$
$(W, F \wedge G)$	Abelard chooses between (w, F) and (w, G)
$(w, F \lor G)$	Heloise chooses between (w, F) and (w, G)



Correctness

Theorem

For the evaluation games for a formula φ and a world w for Routleys' systems, we have the following:

- 1. Heloise has a winning strategy if φ **r**1.
- 2. Abelard has a winning strategy if $\varphi \mathbf{r}$ 0.



< 行 →

∃ >

Classical	LP	FDE	Connexive	B4	LP vs S5	Conclusion	References

Connexive Logic



Game Semantics for Paraconsistent Logics

Can Başkent

< ロ > < 同 > < 三 > < 三

McCall's Connexive Logic

Connexive logic is a "comparatively little-known and to some extent neglected branch of non-classical logic" (Wansing, 2015). Even if it is under-studied, its philosophical roots can be traced back to Aristotle and Boethius.

Connexive logic is defined as a system which satisfies the following two schemes of conditionals:

- Aristotle's Theses: $\neg(\neg \phi \rightarrow \phi)$
- ▶ Boethius' Theses: $(\phi \rightarrow \neg \psi) \rightarrow \neg (\phi \rightarrow \psi)$

In this work, we discuss one of the earliest examples of connexive logics CC, which is due to McCall (McCall, 1966).

McCall's Connexive Logic

CC is axiomatized by adding the scheme $(\varphi \rightarrow \varphi) \rightarrow \neg (\varphi \rightarrow \neg \varphi)$ to the propositional logic. The rules of inference for CC is modus ponens and adjunction, which is given as $\vdash \varphi, \vdash \psi .. \vdash \varphi \land \psi$.

The semantics for CC is given with 4 truth values: *T*, *t*, *f* and *F* which can be viewed as "logical necessity", "contingent truth", "contingent falsehood", and "logical impossibility" respectively (Routley & Montgomery, 1968).

In CC, the designated truth values are T and t.



A ∰ ▶ A ≣ ▶

McCall's Connexive Logic



First, we introduce 4 players for 4 truth values: T is forced by Heloise, F by Abelard, t by Aristotle and f by Boethius.

As the *trues* and *falses* are closed under the binary operations respectively, we suggest the following coalitions.

Truth-maker Coalition:

Heloise (T) and Aristotle (t)

False-maker Coalition:

Abelard (F) and Boethius (f)



< 17 ▶

As the *trues* and *falses* are closed under the binary operations respectively, we suggest the following coalitions.

Truth-maker Coalition:

Heloise (T) and Aristotle (t)

False-maker Coalition:

Abelard (F) and Boethius (f)



- E - >

Game	Rul	es f	for	CC

р	whoever has <i>p</i> in their extension, wins
$\neg F$	switch the roles: Heloise assumes Abelard's role,
	Aristotle assumes Boethius' role,
	Boethius assumes Aristotle's role,
	Abelard assumes Heloise's role, and
	the game continues with <i>F</i>
$F \wedge G$	false-makers coalition chooses between
	F and G
$F \lor G$	truth-makers coalition chooses between
	F and G



◆□ ▶ ◆圖 ▶ ◆ 圖 ▶ ◆ 圖 ▶

Theorem

For the evaluation games for a formula φ in McCall's Connexive logic, we have the following:

- truth-makers have a winning strategy if and only if φ has the truth value t or T in M,
- false-makers have a winning strategy if and only if φ has the truth value f or F in M.



Classical	LP	FDE	Connexive	B4	LP vs S5	Conclusion	References

Belnap's 4-Valued Logic



Game Semantics for Paraconsistent Logics

Can Başkent

Belnap's 4-Valued system, call it B4, introduces two non-classical truth values. Traditionally, *P* stands for both truth values and *N* stands for neither of the truth values.

	–	Λ	T	P	N	F		V	Т	P	Ν	F
Т	F	Т	T	Ρ	Ν	F	-	Т	Т	Т	Т	T
Ρ	Р	Ρ	P	P	F	F		Ρ	Т	P	Т	P
Ν	Ν	Ν	N	F	N	F		Ν	Т	T	Ν	N
F	Т	F	F	F	F	F		F	Т	P	Ν	F

Notice that P and N are the fixed-points under negation.



Belnap's 4-Valued system, call it B4, introduces two non-classical truth values. Traditionally, *P* stands for both truth values and *N* stands for neither of the truth values.

	–	٨	T	P	Ν	F	V	Т	P	Ν	F
Т	F	T	Т	Ρ	Ν	F	 Т	Т	Т	Т	T
Ρ	Р	Ρ	P	P	F	F	Ρ	Т	P	Т	P
Ν	Ν	Ν	N	F	Ν	F	Ν	Т	T	Ν	N
F	T	F	F	F	F	F	F	Т	P	Ν	F

Notice that P and N are the fixed-points under negation.



References

Game Rules for B4

From a game-semantics perspective, the problems with B4 include

- Two fixed-points for negation
- Non-monotonicity: two truth values may produce a third truth value under binary connectives

In particular, we have $P \land N = F$ and $P \lor N = T$.



Let us have 4 players for 4 truth values:

The truth value T is forced by Heloise, F by Abelard, P by Astrolabe and N by Bernard¹.

Two negation-fixed-points suggest that Astrolabe and Bernard both will be the concurrent players.



¹After Abelard's rival Bernard of Clairvaux.

Classical LP FDE RR Connexive B4 LP vs S5 Conclusion References

Game Rules for B4

р	whoever has <i>p</i> in their extension, wins
$\neg F$	Heloise assumes Abelard's role,
	Abelard assumes Heloise's role,
	Astrolabe and Bernard keep their previous roles,
	and the game continues with <i>F</i> ,
$F \wedge G$	if Bernard has a winning strategy for F
	and Astrolabe has a winning strategy for <i>G</i> ,
	then Abelard wins,
$F \wedge G$	otherwise Abelard, Astrolabe and Bernard choose
	simultaneously between F and G,
$F \lor G$	if Bernard has a winning strategy for F
	and Astrolabe has a winning strategy for <i>G</i> ,
	then Heloise wins,
$F \lor G$	otherwise Heloise, Astrolabe and Bernard choose
	simultaneously between F and G. \mathcal{B} \mathcal{B} \mathcal{B} \mathcal{B}

Theorem

For the evaluation games for a formula φ in Belnap's 4-valued logic, we have the following:

- Heloise the verifier has a winning strategy if φ evaluates to T,
- Abelard the falsifier has a winning strategy if φ evaluates to F,
- Astrolabe the paradoxifier has a winning strategy if φ evaluates to P,
- Bernard the nullifier has a winning strategy if φ evaluates to *N*.

VERSITY OF

Classical	LP	FDE	Connexive	B4	LP vs S5	Conclusion	References

Translation to Classical S5



Game Semantics for Paraconsistent Logics

Can Başkent

The translation of LP to S5 is built on the following observation:

"In an S5-model there are three mutually exclusive and jointly exhaustive possibilities for each atomic formula p: either p is true in all possible worlds, or p is true in some possible worlds and false in others, or p is false in all possible worlds" (Kooi & Tamminga, 2013).



Classical LP FDE RR Connexive B4 LP vs S5 Conclusion References Translation

Given the propositional language \mathcal{L} , we extend it with the modal symbols \Box and \Diamond and close it under the standard rules to obtain the modal language \mathcal{L}_M . Then, the translations $\operatorname{Tr}_{LP} : \mathcal{L} \mapsto \mathcal{L}_M$ and $\operatorname{Tr}_{K3} : \mathcal{L} \mapsto \mathcal{L}_M$ for LP and K3 respectively are given inductively as follows where p is a propositional variable (Kooi & Tamminga, 2013).

$$Tr_{LP}(p) = \Diamond p$$

$$Tr_{K3}(p) = \Box p$$

$$Tr_{LP}(\neg \varphi) = \neg Tr_{K3}(\varphi)$$

$$Tr_{K3}(\neg \varphi) = \neg Tr_{LP}(\varphi)$$

$$\begin{array}{l} \operatorname{Tr}_{LP}(\varphi \land \psi) = \operatorname{Tr}_{LP}(\varphi) \land \operatorname{Tr}_{LP}(\psi) \\ \operatorname{Tr}_{K3}(\varphi \land \psi) = \operatorname{Tr}_{K3}(\varphi) \land \operatorname{Tr}_{K3}(\psi) \\ \operatorname{Tr}_{LP}(\varphi \lor \psi) = \operatorname{Tr}_{LP}(\varphi) \lor \operatorname{Tr}_{LP}(\psi) \\ \operatorname{Tr}_{K3}(\varphi \lor \psi) = \operatorname{Tr}_{K3}(\varphi) \lor \operatorname{Tr}_{K3}(\psi) \end{array}$$



Translation: Toy Examples

Contradictions are possible in LP, but not in K3.

$$\operatorname{Tr}_{LP}(p \land \neg p) = \operatorname{Tr}_{LP}(p) \land \operatorname{Tr}_{LP}(\neg p)$$
$$= \Diamond p \land \neg \operatorname{Tr}_{K3}(p)$$
$$= \Diamond p \land \neg \Box p$$
$$- \Diamond p \land \Diamond \neg p$$

LP vs S5

$$Tr_{K3}(p \land \neg p) = Tr_{K3}(p) \land Tr_{K3}(\neg p)$$

= $\Box p \land \neg Tr_{LP}(p)$
= $\Box p \land \neg \Diamond p$
= $\Box p \land \Box \neg p.$

Can Başkent

<ロト < 回 > < 回 > < 回 > <</p>

Ή

Classical	LP	FDE	Connexive	B4	LP vs S5	Conclusion	References
Resul	ts						

Theorem

Let $\Gamma_{LP}(M, \varphi)$ be given. Then,

- ► if Heloise has a winning strategy in $\Gamma_{LP}(M, \varphi)$, then she has a winning strategy in $\Gamma_{S5}(M, \text{Tr}_{LP}(\varphi))$,
- ► if Abelard has a winning strategy in $\Gamma_{LP}(M, \varphi)$, then he has a winning strategy in $\Gamma_{S5}(M, \text{Tr}_{LP}(\varphi))$,
- if Astrolabe has a winning strategy in $\Gamma_{LP}(M, \varphi)$, then both Abelard and Heloise have a winning strategy in $\Gamma_{S5}(M, \operatorname{Tr}_{LP}(\varphi))$.



• □ ▶ • • □ ▶ • □ ▶

Classical	LP	FDE	Connexive	B4	LP vs S5	Conclusion	References
Resul	lts						

Theorem

Let *M* be an S5 model, $\varphi \in \mathcal{L}$ with an associated verification game $\Gamma_{S5}(M, \varphi)$. Then, there exists an LP model *M'* and a game $\Gamma_{LP}(M', \varphi)$ where,

- if Heloise (resp. Abelard) has a winning strategy for $\Gamma_{S5}(M, \varphi)$ at each point in M, then Heloise (resp. Abelard) has a winning strategy in $\Gamma_{LP}(M', \varphi)$,
- if Heloise or Abelard has a winning strategy for $\Gamma_{S5}(M, \varphi)$ at some points but not all in M, then Astrolabe has a winning strategy in $\Gamma_{LP}(M', \varphi)$,



Classical	LP	FDE	Connexive	B4	LP vs S5	Conclusion	References

Conclusion



Game Semantics for Paraconsistent Logics

Can Başkent

What Have We Observed?

- Failure of the biconditional correctness
- Multiplayer semantic games in a nontrivial way
- Non-sequential / paralel / concurrent plays
- Variable sum games
- Coalitions

If winning strategies are proofs, game semantics for paraconsistent logics present a constructive way to give proofs for inconsistencies.



・ 同 ト ・ 三 ト ・

What Have We Observed?

- Failure of the biconditional correctness
- Multiplayer semantic games in a nontrivial way
- Non-sequential / paralel / concurrent plays
- Variable sum games
- Coalitions

If winning strategies are proofs, game semantics for paraconsistent logics present a constructive way to give proofs for inconsistencies.

< 17 ▶

- E ►



- Da Costa systems, Logics of Formal Inconsistency
- Preservationism
- First-order paraconsistent logics
- Infinitary, fixed-point non-classical logics

< 17 ▶

Generalized Game Semantics

Based on our observations here, by focusing on the truth values which are

- negation-fixed-points (parallel plays) and
- closed under binary operations (coalitions),

it could be possible to give game semantics for any finite truth table.





I consider this work as a very first step towards paraconsistent / non-classical game theory.

Our long term goal is to give a broader theory of (non-classical, non-utilitarian) rationality via games and logic.



< 177 ▶



Talk slides and the paper are available at: www.CanBaskent.net/Logic



Perspectives on Interrogative Models of Inquiry

< 177 ▶

< ∃ >

Ed. Can Başkent, Springer.



Game Semantics for Paraconsistent Logics

Classical	LP	FDE	Connexive	B4	LP vs S5	Conclusion	References
Refer	enc	es l					

Dunn, J. Michael. 1976.

Intuitive Semantics for First-Degree Entailments and 'Coupled Trees'.

Philosophical Studies, 29(3), 149–168.

Kooi, Barteld, & Tamminga, Allard. 2013.

Three-valued Logics in Modal Logic.

Studia Logica, 101(5), 1061-1072.

McCall, Storrs. 1966.

Connexive Implication.

Journal of Symbolic Logic, 31(3), 415–433.

Priest, Graham. 1979.

The Logic of Paradox.

Journal of Philosophical Logic, 8, 219–241.

Routley, R., & Routley, V. 1972.

The Semantics of First Degree Entailment.

Noûs, **6**(4), 335–359.



Can Başkent

< ∃ >

Game Semantics for Paraconsistent Logics

Routley, Richard, & Montgomery, H. 1968.

On Systems Containing Aristotle's Thesis.

The Journal of Symbolic Logic, **33**(1), 82–96.

Wansing, Heinrich. 2015.

Connexive Logic.

In: Zalta, Edward N. (ed), The Stanford Encyclopedia of Philosophy, fall 2015 edn.



Can Başkent

< ロ > < 部 > < 目 > <</p>

Game Semantics for Paraconsistent Logics